

"The Professional's Choice"™

SUBMITTAL SHEET

Submittal Sheet #03090413

GRABBER® Pan Head Streaker®

| Product: | ltem# | Description | Unit Pack |
|----------|-------|---|-----------|
| | 23 | Pan Head STREAKER 7 x 7/16", Bulk (15TPI) | 15 M |
| | 23A | Pan Head STREAKER 7 x 7/16", Bulk (15TPI) (Made in USA) | 15 M |
| | 23F | Pan Head STREAKER 7 x 7/16", Bulk (20 TPÍ) | 15 M |

Grabber American Made Screws with the item numbers ending in "A" are manufactured by Brynolf Manufacturing, Rockford, Illinios. Grabber Construction Products is the exclusive distributor of Grabber American Made Screws Grabber American Made Screws have a unique identification head stamp mark "*". Grabber American Made Screws are SPECIAL ORDER INVENTORY. CONTACT GRABBER FOR CURRENT PRICE AND AVAILABILITY.

| Application: | Designed specifically for framing light gauge metal to light gauge metal stud. (20 - 25 gauge) Also used for strapping, HVAC assembly applications. | | |
|--------------|---|--|--|
| | | | |
| Description: | GRABBER Pan Head Streaker Screws are designed for use with light gauge steel (20-25 gauge) Choice of 15 or 20 Threads per Inch. Grey phosphate, clear zinc or GrabberGard® coatings. HiTorque head design. | | |
| Directions: | Use standard screw gun with depth sensitive nose piece. Suggested screw gun for optimium performance is 4 amps minimum and 0 to 4,000 rpm. Pan Head is completely seated when the head is against the work surface. Overdriving may result in failure of the fastener, the metal the fastener is attaching to or stripping of the head recess. Penetration of three thread pitches beyond the | | |

penentrated metal is minimum.



Pan head streaker

Page: 1/3

SUBMITTAL APPROVALS: JOB NAME **CONTRACTOR** DATE **NOTICE:** TRADEMARKS: The following trademark used herein is owned by Grabber We shall not be liable for incidental and consequential Construction Products, Inc.: GRABBER, STREAKER. damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our liability is expressly limited to replacement of defective

goods. Any claim shall be (30) days of the date it was or

reasonably should have been discovered.

Product #216

Pan Framing Head STREAKER®





Head





23° Streaker® Point

#2 Phillip

PRODUCT FEATURES

Used in light gauge metal to metal applications where high torque is required. Super sharp 30° Streaker Point means quick and easy penetration.

- ▶A fine thread screw for metal-to-metal framing applications
- ▶ 15 or 20 threads per inch
- ▶ High torque Pan Framing Head
- ▶ Super sharp, 23° STREAKER® point, designed to penetrate steel quickly and easily
- ▶ #2 Phillips recess drive

SPECIFICATIONS

- ▶ Gauge #7
- ▶ Length 7/16"
- ▶ Head Type Pan Framing
- ▶ Recess Type #2 Phillips
- ▶ Thread Type Double Lead
- ▶ Finish Gray Phosphate
- ► GRABBER® screws are manufactured in an ISO 9002 and ISO 14001 certified and approved factory, and are approved by ICC ER #5280.

STANDARD CORROSION TEST RESULTS

| FIIIISII | iesi | Sialiaara/Protocol | Kesuiis |
|------------|------------|--------------------|-------------|
| Black/Gray | Salt Spray | ASTM B117 | 24 hours, |
| Phosphate | Results | | No Red Rust |

All GRABBER® screw products are manufactured in facilities that are ISO 9002 and ISO 14001 certified and approved. The fasteners comply with ASTM C1513, as referenced in ICC ESR report ESR-1271, are approved for use in structures governed by the International Building Code 2006, 2009, 2012, International Residential Building Code 2006, 2009, and 2012.







