



Radars Ceilings

USG

Technical Service 800.950.4900
 Customer Service 800.950.3839
 For drawings, product information
 or literature visit usg.com
 and usgdesignproducts.com

Radars™ Ceilings

Grid Profile Options

Edge	Panel Size	Class	Item No.	VOC Emissions	NRC	Min. CAC	LR	Grid Options	Recycled Content	Colors	ASTM E1294 classification	ASTM E84 surface burning characteristics	Thermal resistance	Substrate	Product Information
SO	2' x2' x5/8"	Class A	2110	ME2110	.55	.83	A, B, C	24-28%	41-49%	Available in White only	Class A, Frame spread: 25"	Smoke developed: 50	R-1.4 (Class A, 5/8" panels and tile)	Water-felted mineral fiber.	See usg.com for the most up-to-date product information. Data sheet: SC2288
	2' x2' x5/8"	Class A	2310	ME2310	.55	.83	A, B	24-28%	41-49%		Type III, Form 2, Pattern C, E	ASTM E84 surface burning characteristics	R-1.4 (Class A, 5/8" panels and tile)		
	2' x4' x5/8"	Class A	2315	ME2315	.55	.83	A	24-28%	41-49%				R-1.4 (Class A, 5/8" panels and tile)		
	2' x4' x5/8"	Class A	2619	ME2619	.55	.83	A, B	24-28%	41-49%				R-1.4 (Class A, 5/8" panels and tile)		
	2' x4' x5/8"	Class A	2617	ME2617	.55	.83	A, B	24-28%	41-49%				R-1.4 (Class A, 5/8" panels and tile)		
	30" x60" x3/4"	Class A	2618	ME2618	.60	.83	A, B	24-28%	41-49%				R-1.4 (Class A, 5/8" panels and tile)		
SLT	2' x2' x5/8"	Class A	2120	ME2120	.55	.83	D	24-29%	49-58%				R-1.4 (Class A, 5/8" panels and tile)		
	2' x2' x5/8"	Class A	2125	ME2125	.55	.83	D	24-29%	49-58%				R-1.4 (Class A, 5/8" panels and tile)		
	2' x4' x5/8"	Class A	2320	ME2320	.55	.83	D	24-29%	49-58%				R-1.4 (Class A, 5/8" panels and tile)		
FLB	2' x2' x5/8"	Class A	2130	ME2130	.55	.83	E, F, G, I	24-29%	49-58%				R-1.4 (Class A, 5/8" panels and tile)		
BESK	12' x12' x5/8"	Class A	2990	ME2990	.50	.83	H	44%	49-58%				R-1.4 (Class A, 5/8" panels and tile)		

Manufactured by USG Interiors, LLC
 550 West Adams Street
 Chicago, IL 60661

This sample is a general representation of the texture and color of the ceiling product named above. Do not use for dimensional measurement or physical testing.

© 2013, USG Interiors, LLC
 Printed in U.S.A.



Low-Emitting performance meets CA Specification 01350 (CA Dept. of Health Services Standard Practice for the testing of VOC emissions) and is listed on CHPS data base for low-emitting materials. USG Certificate of Compliance for Low VOC Emissions also available on usg.com

Not UL Classified for acoustics.
 Recycled content not available at all plants.